

RoHS Compliant Product  
A suffix of "-C" specifies halogen & lead-free



## FEATURE

- Power Dissipation

## CLASSIFICATION OF $h_{FE}$ (1)

Product-Rank	C1815T-O	C1815T-Y	C1815T-GR
Range	70~140	120~240	200~400

## TO-92



## ABSOLUTE MAXIMUM RATINGS ( $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Ratings	Unit
Collector to Base Voltage	$V_{CBO}$	60	V
Collector to Emitter Voltage	$V_{CEO}$	50	V
Emitter to Base Voltage	$V_{EBO}$	5	V
Collector Current - Continuous	$I_C$	150	mA
Collector Power Dissipation	$P_C$	400	mW
Junction, Storage Temperature	$T_J, T_{STG}$	125, -55 ~ 125	$^\circ\text{C}$

## ELECTRICAL CHARACTERISTICS ( $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test condition
Collector to Base Breakdown Voltage	$V_{(BR)CBO}$	60	-	-	V	$I_C=100\mu\text{A}, I_E=0$
Collector to Emitter Breakdown Voltage	$V_{(BR)CEO}$	50	-	-	V	$I_C=0.1\text{mA}, I_B=0$
Emitter to Base Breakdown Voltage	$V_{(BR)EBO}$	5	-	-	V	$I_E=100\mu\text{A}, I_C=0$
Collector Cut-Off Current	$I_{CBO}$	-	-	0.1	$\mu\text{A}$	$V_{CB}=60\text{V}, I_E=0$
Collector Cut-Off Current	$I_{CEO}$	-	-	0.1	$\mu\text{A}$	$V_{CE}=50\text{V}, I_B=0$
Emitter Cut-Off Current	$I_{EBO}$	-	-	0.1	$\mu\text{A}$	$V_{EB}=5\text{V}, I_C=0$
DC Current Gain	$h_{FE}$	70	-	700	-	$V_{CE}=6\text{V}, I_C=2\text{mA}$
Collector to Emitter Saturation Voltage	$V_{CE(sat)}$	-	-	0.25	V	$I_C=100\text{mA}, I_B=10\text{mA}$
Base to Emitter Saturation Voltage	$V_{BE(sat)}$	-	-	1	V	$I_C=100\text{mA}, I_B=10\text{mA}$
Transition Frequency	$f_T$	80	-	-	MHz	$V_{CE}=10\text{V}, I_C=1\text{mA}, f=30\text{MHz}$
Collector Output Capacitance	$C_{ob}$	-	-	3.5	pF	$V_{CB}=10\text{V}, I_E=0, f=1\text{MHz}$
Noise Figure	NF	-	-	10	dB	$V_{CE}=6\text{V}, I_C=0.1\text{mA}, f=1\text{KHz}, R_G=10\text{K}\Omega$

**CHARACTERISTIC CURVES**

