

RoHS Compliant Product  
A suffix of "-C" specifies halogen & lead-free

## FEATURES

- High Current Capability
- High DC Current Gain
- Small Package


## APPLICATIONS

- Audio Amplifier Applications
- AM Amplifier Applications

## CLASSIFICATION OF $h_{FE}$

Product-Rank	2SC4115S-Q	2SC4115S-R	2SC4115S-S
Range	120~270	180~390	270~560

## TO-92S



## ABSOLUTE MAXIMUM RATINGS ( $T_A=25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Rating	Unit
Collector to Base Voltage	$V_{CBO}$	40	V
Collector to Emitter Voltage	$V_{CEO}$	20	V
Emitter to Base Voltage	$V_{EBO}$	6	V
Collector Current - Continuous	$I_C$	3	A
Collector Power Dissipation	$P_C$	300	mW
Thermal Resistance From Junction To Ambient	$R_{\theta JA}$	417	$^\circ\text{C} / \text{W}$
Junction, Storage Temperature	$T_J, T_{STG}$	150, -55~150	$^\circ\text{C}$

## ELECTRICAL CHARACTERISTICS ( $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Condition
Collector to Base Breakdown Voltage	$V_{(BR)CBO}$	40	-	-	V	$I_C=0.05\text{mA}, I_E=0$
Collector to Emitter Breakdown Voltage	$V_{(BR)CEO}$	20	-	-	V	$I_C=1\text{mA}, I_B=0$
Emitter to Base Breakdown Voltage	$V_{(BR)EBO}$	6	-	-	V	$I_E=0.05\text{mA}, I_C=0$
Collector Cut - Off Current	$I_{CBO}$	-	-	0.1	$\mu\text{A}$	$V_{CB}=30\text{V}, I_E=0$
Emitter Cut - Off Current	$I_{EBO}$	-	-	0.1	$\mu\text{A}$	$V_{EB}=5\text{V}, I_C=0$
DC Current Gain	$h_{FE}$	120	-	560		$V_{CE}=2\text{V}, I_C=100\text{mA}$
Collector to Emitter Saturation Voltage	$V_{CE(sat)}$	-	-	0.5	V	$I_C=2\text{A}, I_B=100\text{mA}$
Collector Output Capacitance	$C_{ob}$	-	25	-	pF	$V_{CB}=10\text{V}, I_E=0, f=1\text{MHz}$
Transition Frequency	$f_T$	-	290	-	MHz	$V_{CE}=2\text{V}, I_C=0.5\text{A}, f=100\text{MHz}$