

RoHS Compliant Product
A suffix of "-C" specifies halogen & lead-free


FEATURES

- High Current Capability
- Extremely Low Thermal Resistance
- For Surface Mount Application
- Higher Temp Soldering : 250°C for 10 Seconds at Terminals
- Low Reverse Current

MECHANICAL DATA

- Case: Molded Plastic
- Epoxy: UL 94V-0 Rate Flame Retardant
- Lead: Axial Leads, Solderable per MIL-STD-202 method 208 Guaranteed
- Polarity: Color Band Denotes Cathode End
- Mounting Position: Any

SMA



PACKAGE INFORMATION

Package	MPQ	Leader Size
SMA	5K	13 inch

REF.	Millimeter		REF.	Millimeter	
	Min.	Max.		Min.	Max.
A	1.24	1.65	E	-	0.203
B	3.99	4.60	F	4.80	5.28
C	2.50	2.90	G	0.76	1.52
D	1.98	2.44	H	0.15	0.305

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

(Rating 25°C ambient temperature unless otherwise specified. Single phase half wave, 60Hz, resistive or inductive load.
For capacitive load, de-rate current by 20%.)


Parameter	Symbol	Rated	Unit
Peak Repetitive Peak Reverse Voltage	V_{RRM}	100	V
Working Peak Reverse Voltage	V_{RWM}	100	V
Maximum DC Blocking Voltage	V_R	100	V
Average Forward Current @ $T_J=25^\circ\text{C}$	$I_{F(AV)}$	5	A
Peak Forward Current @ 8.3ms Half Sine	I_{FSM}	125	A
Maximum Instantaneous Forward Voltage	V_F	$I_{FM}=5.0A, T_A=25^\circ\text{C}$	0.82
		$I_{FM}=5.0A, T_A=75^\circ\text{C}$	0.73
		$I_{FM}=5.0A, T_A=125^\circ\text{C}$	0.65
Maximum DC Reverse Current At Rated DC Blocking Voltage ⁴	I_R	$T_J=25^\circ\text{C}$	100
		$T_J=100^\circ\text{C}$	800
Typical Junction Capacitance	C_J	350	pF
Typical Thermal Resistance ²	$R_{\theta JA}$	55	$^\circ\text{C} / \text{W}$
Typical Thermal Resistance ³	$R_{\theta JC}$	20	$^\circ\text{C} / \text{W}$
Device Power Dissipation	P_D	2	W
Voltage Rate of Change (Rated V_R)	dv/dt	10000	V / μs
Operating and Storage Temperature Range	T_J, T_{STG}	-50~150, -65~150	$^\circ\text{C}$

Notes:


1. Measured at 1MHz and applied reverse voltage of 5.0V D.C.
2. Thermal Resistance Junction to Ambient.
3. Thermal Resistance Junction to Case.
4. Pulse Test : Pulse Width $\leq 300\mu\text{s}$, Duty Cycle $\leq 2.0\%$.

RATINGS AND CHARACTERISTIC CURVES


Typical Forward Current Derating Curve




Typical Forward Characteristic



Maximum Non- Repetitive Forward Surge Current



Typical Reverse Characteristic



Typical Junction Capacitance

