

RoHS Compliant Product
A suffix of "-C" specifies halogen & lead-free


DESCRIPTION

The STESD05C-C is designed to protect voltage sensitive components from ESD. Excellent clamping capability, low leakage, and fast response time provide best in class protection on designs that are exposed to ESD. Because of its small size, it is suited for use in cellular phones, MP3 players, digital cameras and many other portable applications where board space is at a premium.

FEATURES

- Bi-Directional ESD Protection of One Line
- Stand-off voltage: 5V
- Low Reverse Clamping Voltage
- Low Leakage Current
- Response Time is Typically <1ns
- ESD Rating of Class 3 (>16kV) per Human Body Model
- IEC61000-4-2 Level 4 ESD Protection
- IEC61000-4-4 Level 4 EFT Protection

WBFBP-02C



REF.	Millimeter		REF.	Millimeter	
	Min.	Max.		Min.	Max.
A	0.95	1.05	G	0.25	0.35
B	0.55	0.65	H	0.25	0.35
C	0.44	0.55	J	0.275	0.47
D	0.470 REF.		K	0.555	0.725
E	0.420 REF.		L	0.010	0.100
F	0.27	0.37	M	0.030 REF.	

MARKING



PACKAGE INFORMATION

Package	MPQ	Leader Size
WBFBP-02C	10K	7 inch

ORDER INFORMATION

Part Number	Type
STESD05C-C	Lead (Pb)-free and Halogen-free


MAXIMUM RATINGS (T_A=25°C)

Parameter	Symbol	Ratings	Unit
IEC 61000-4-2 (ESD)	Air	±25	KV
	Contact	±25	
ESD Voltage	Per Human Body Model	±16	KV
	Per Machine Model	400	V
Total Power Dissipation on FR-5 Board ¹	P _D	100	mW
Thermal Resistance Junction-Ambient	R _{θJA}	1250	°C/W
Lead Solder Temperature-Maximum (10 Second Duration)	T _L	260	°C
Junction and Storage Temperature Range	T _J , T _{STG}	-55~150	°C

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended. Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

Note:

1. FR-5 = 1.0 x 0.75 x 0.62 in.



ELECTRICAL CHARACTERISTICS ($T_A=25^\circ\text{C}$ unless otherwise noted.)


Parameter	Symbol	Min.	Typ.	Max.	Unit
Working Peak Reverse Voltage	V_{RWM}	-	-	5	V
Maximum Reverse Leakage Current @ V_{RWM}	I_R	-	-	1	μA
Breakdown Voltage @ I_T^2	V_{BR}	5.8	-	8.8	V
Test Current	I_T	-	-	1	mA
Maximum Reverse Peak Pulse Current ³	I_{PP}	-	-	8	A
Clamping Voltage @ I_{PP}^3	V_C	-	-	15	V
Max. Capacitance @ $V_R=0$ and $f=1\text{MHz}$	C_J	-	27	-	pF

Notes:


- V_{BR} is measured with a pulse test current I_T at an ambient temperature of 25°C .
- Test by $T_p=8/20\mu\text{s}$ pulse waveform.

CHARACTERISTICS CURVES

Reverse Characteristics



V_C — I_{PP}



Capacitance Characteristics

